

COMPOSITION SYSTEM

LINEAR ADJUSTABLE

Modular LED linear adjustable fixture with 180 deg. tilt angle. Fixture is easily repositioned and connected automatically with mechanical quick connect fitting.



Project _____

Date _____

Type _____



ORDERING INFORMATION

MODEL	CCT	FINISH	CRI	WATT	BEAM ANGLE	VOLT	DIMMING
COCO-HTE-9620	27- 2700K 30- 3000K 35- 3500K	W- White B- Black	90- 90CRI	9- 9W	110- 110 °	42- 42V	N- Non Dim D- 1-10V Dim
COCO-HTE-9620							

LUMEN OUTPUT & WATTAGE (BASE ON 3000K)

	COCO-HTE-9620
Wattage	9 W
Delivered Lumen	385 lm

LUMEN MULTIPLIER

	COCO-HTE-9620		
CCT	2700k	3000k	3500k
Factor	0.99	1	1.02

FIXTURE SPECIFICATION

LED CHIPS

Samsung LED

HOUSING

Aluminum body

MECHANICAL

Fixture have 180 degree tilt angle.

WARRANTY

5 year warranty.

IP RATED



IP20 rated, dry location only.

LISTING

ETL listing, CE listing

PHOTOMETRIC CURVES

COCO-HTE-9620



AT 3000K, 90CRI
3000K- 110° BEAM