

# COMPOSITION SYSTEM

## LINEAR INSERT

Modular linear insert available in 4 standard sizes.



Project \_\_\_\_\_

Date \_\_\_\_\_

Type \_\_\_\_\_

### ORDERING INFORMATION

MODEL	CCT	FINISH	CRI	WATT	BEAM ANGLE	VOLT	DIMMING	LENGTH
COCO-LBE-9473	27- 2700K 30- 3000K 35- 3500K	W- White B- Black	90- 90CRI	6- 6W	110- 110°	42- 42V	N- Non Dim D- 1-10V Dim	8"L
COCO-LBE-9474				13- 13W				16"L
COCO-LBE-9475				21- 21W				31"L
COCO-LBE-9476				35- 35W				47"L
COCO-LBE-								

### LUMEN OUTPUT & WATTAGE (BASE ON 3000K)

	COCO-LBE-9473A	COCO-LBE-9474A	COCO-LBE-9475A	COCO-LBE-9476A
Wattage	6 W	13 W	21 W	35 W
Lumen Package	385 lm	783 lm	1470 lm	2541 lm

### LUMEN MULTIPLIER

	COCO-LBE-9473A			COCO-LBE-9474A			COCO-LBE-9475A			COCO-LBE-9476A		
CCT	2700K	3000K	3500K	2700K	3000K	3500K	2700K	3000K	3500K	2700K	3000K	3500K
Factor	0.99	1	1.02	0.99	1	1.02	0.99	1	1.02	0.99	1	1.02

## FIXTURE SPECIFICATION

### LED CHIPS

Samsung LED

### HOUSING

Aluminum body

### WARRANTY

5 year warranty.

### IP RATED



IP20 rated, dry location only.

### LISTING

ETL listing, CE listing



## PHOTOMETRIC CURVES

### COCO-LBE-9473





AT 3000K, 90CRI  
3000K- 110° BEAM

### COCO-LBE-9474





AT 3000K, 90CRI  
3000K- 110° BEAM

### COCO-LBE-9475



AT 3000K, 90CRI  
3000K- 110° BEAM

### COCO-LBE-9476



AT 3000K, 90CRI  
3000K- 110° BEAM