

# COMPOSITION SYSTEM

## TOOB

Sleek cylindrical pendant fixture.



Project \_\_\_\_\_

Date \_\_\_\_\_

Type \_\_\_\_\_



### ORDERING INFORMATION

MODEL	CCT	FINISH	CRI	WATT	BEAM ANGLE	VOLT	DIMMING
COCO-LPE-9311	27- 2700K 30- 3000K 35- 3500K	W- White B- Black	90- 90CRI	8- 7.7W	27- 27° 45- 45°	42- 42V	N- Non Dim D- 1-10V Dim
COCO-LPE-9321				18- 18.2W	20- 20° 32- 32° 45- 45°		
COCO-LPE-							

### LUMEN OUTPUT & WATTAGE (BASE ON 3000K)

	COCO-LPE-9311			COCO-LPE-9321		
<b>Wattage</b>	7.7 W			18.6 W		
<b>Beam Angle</b>	27°	45°		20°	32°	45°
<b>Delivered Lumen</b>	522 lm	487 lm		1499 lm	1469 lm	1216 lm

### LUMEN MULTIPLIER

	COCO-LPE-9311			COCO-LPE-9321		
<b>CCT</b>	2700k	3000k	3500k	2700k	3000k	3500k
<b>Factor</b>	0.95	1	1.01	0.94	1	1.01

## FIXTURE SPECIFICATION

### LED CHIPS

CREE LED

### HOUSING

Aluminum body

### WARRANTY

5 year warranty.

### IP RATED


IP20 rated, dry location only.

### LISTING


ETL listing, CE listing

## PHOTOMETRIC CURVES


### COCO-LPE-9311



\*UNIT: CD




AT 3000K, 90CRI  
3000K- 27° BEAM




3000K- 45° BEAM


### COCO-LPE-9321




\*UNIT: CD



AT 3000K, 90CRI  
3000K- 20° BEAM



3000K- 32° BEAM



3000K- 45° BEAM