

COMPOSITION SYSTEM

TOOB

Sleek cylindrical pendant fixture.



Project _____

Date _____

Type _____



ORDERING INFORMATION

MODEL	CCT	FINISH	CRI	WATT	BEAM ANGLE	VOLT	DIMMING
COCO-LPE-9311	27- 2700K 30- 3000K 35- 3500K	W- White B- Black	90- 90CRI	8- 7.7W	27- 27° 45- 45°	48	N- Non Dim D- 1-10V Dim
COCO-LPE-9321				18- 18.2W	20- 20° 32- 32° 45- 45°		
COCO-LPE-							

LUMEN OUTPUT & WATTAGE (BASE ON 3000K)

	COCO-LPE-9311			COCO-LPE-9321		
Wattage	7.7 W			18.6 W		
Beam Angle	27°	45°		20°	32°	45°
Delivered Lumen	522 lm	487 lm		1499 lm	1469 lm	1216 lm

LUMEN MULTIPLIER

	COCO-LPE-9311			COCO-LPE-9321		
CCT	2700k	3000k	3500k	2700k	3000k	3500k
Factor	0.95	1	1.01	0.94	1	1.01

FIXTURE SPECIFICATION

LED CHIPS

CREE LED

HOUSING

Aluminum body

WARRANTY

5 year warranty.

IP RATED


IP20 rated, dry location only.

LISTING


ETL listing, CE listing

PHOTOMETRIC CURVES


COCO-LPE-9311



*UNIT: CD




AT 3000K, 90CRI
3000K- 27° BEAM




3000K- 45° BEAM


COCO-LPE-9321




*UNIT: CD



AT 3000K, 90CRI
3000K- 20° BEAM



3000K- 32° BEAM



3000K- 45° BEAM