

# COMPOSITION SYSTEM

## CUBIST INSERT

Multi-cell optics low glare downlight, available in 3 beam distributions.



Project \_\_\_\_\_

Date \_\_\_\_\_

Type \_\_\_\_\_

### ORDERING INFORMATION

MODEL	CCT	FINISH	CRI	WATT	BEAM ANGLE	VOLT	DIMMING	CELL
COCO-LBE-9483	27- 2700K 30- 3000K 35- 3500K	W- White B- Black	90- 90CRI	11- 11W	20- 20° 36- 36° 48- 48°	48- 48V	D- 0-10V Dim DA- DALI	9- 9 Cells
COCO-LBE-9484				20- 20W				18- 18 Cells
COCO-LBE-9485				39- 39W				27- 27 Cells
COCO-LBE-								

### LUMEN OUTPUT & WATTAGE (BASE ON 3000K)

	COCO-LBE-9483			COCO-LBE-9484			COCO-LBE-9485		
Wattage	11 W			20 W			33 W		
Beam Angle	20°	36°	48°	20°	36°	50°	20°	36°	50°
Delivered Lumen	829 lm	826 lm	794 lm	1607 lm	1632 lm	1544 lm	3319 lm	3422 lm	3167 lm

### LUMEN MULTIPLIER

	COCO-LBE-9483			COCO-LBE-9484			COCO-LBE-9485		
CCT	2700k	3000k	3500k	2700k	3000k	3500k	2700k	3000k	3500k
Factor	0.894	1	1.018	0.894	1	1.018	0.894	1	1.018

## FIXTURE SPECIFICATION

### LED CHIPS

CREE XPE-2 LED

### HOUSING

Aluminum body

### WARRANTY

5 year warranty.

### IP RATED


IP20 rated, dry location only.

### LISTING


ETL listing, CE listing

## PHOTOMETRIC CURVES & FIXTURE DIMENSIONS


### COCO-LBE-9483




\*UNIT: CD



AT 3000K, 90CRI  
3000K- 20° BEAM




3000K- 36° BEAM




3000K- 48° BEAM


### COCO-LBE-9484




\*UNIT: CD



AT 3000K, 90CRI  
3000K- 20° BEAM




3000K- 36° BEAM




3000K- 50° BEAM


### COCO-LBE-9485




\*UNIT: CD



AT 3000K, 90CRI  
3000K- 20° BEAM



3000K- 36° BEAM



3000K- 50° BEAM