

# COMPOSITION SYSTEM

## LINEAR INSERT

Modular linear insert available in 4 standard sizes.



Project \_\_\_\_\_

Date \_\_\_\_\_

Type \_\_\_\_\_

### ORDERING INFORMATION

MODEL	CCT	FINISH	CRI	WATT	BEAM ANGLE	VOLT	DIMMING	LENGTH
COCO-LBE-9473	27- 2700K 30- 3000K 35- 3500K	W- White B- Black	90- 90CRI	6- 6W	110- 110°	48- 48V	N- Non Dim D- 1-10V Dim	8"L
COCO-LBE-9474				13- 13W				16"L
COCO-LBE-9475				19- 19W				31"L
COCO-LBE-9476				35- 35W				47"L
COCO-LBE-								

### LUMEN OUTPUT & WATTAGE (BASE ON 3000K)

	COCO-LBE-9473	COCO-LBE-9474	COCO-LBE-9475	COCO-LBE-9476
Wattage	6 W	11 W	19 W	35 W
Delivered Lumen	385 lm	696 lm	1543 lm	2558 lm

### LUMEN MULTIPLIER

	COCO-LBE-9473			COCO-LBE-9474			COCO-LBE-9475			COCO-LBE-9476		
CCT	2700k	3000k	3500k	2700k	3000k	3500k	2700k	3000k	3500k	2700k	3000k	3500k
Factor	0.99	1	1.02	0.99	1	1.02	0.99	1	1.02	0.99	1	1.02

## FIXTURE SPECIFICATION

### LED CHIPS

Bridgelux 2835 LED

### HOUSING

Aluminum body

### WARRANTY

5 year warranty.

### IP RATED



IP20 rated, dry location only.

### LISTING

ETL listing, CE listing



## PHOTOMETRIC CURVES

### COCO-LBE-9473





AT 3000K, 90CRI  
3000K- 110° BEAM

### COCO-LBE-9474





AT 3000K, 90CRI  
3000K- 110° BEAM

### COCO-LBE-9475



AT 3000K, 90CRI  
3000K- 110° BEAM

### COCO-LBE-9476



AT 3000K, 90CRI  
3000K- 110° BEAM