

COMPOSITION SYSTEM

LINEAR INSERT CORNER

Modular linear insert vertical and horizontal corner.



Project _____

Date _____

Type _____



ORDERING INFORMATION

MODEL	CCT	FINISH	CRI	WATT	BEAM ANGLE	VOLT	DIMMING	CONFIGURATION
COCO-LBE-9410	27- 2700K 30- 3000K 35- 3500K	W- White B- Black	90- 90CRI	9- 9W	110- 110°	48- 48V	D- 0-10V Dim DA- DALI	H- Horizontal Corner
COCO-LBE-9411								I- Vertical Inner Corner
COCO-LBE-9412								O- Vertical Outer Corner
COCO-LBE-								

LUMEN OUTPUT & WATTAGE (BASE ON 3000K)

	COCO-LBE-9410, 9411, 9412
Wattage	9 W
Delivered Lumen	636 lm

LUMEN MULTIPLIER

	COCO-LBE-9410, 9411, 9412		
CCT	2700k	3000k	3500k
Factor	0.99	1	1.04

FIXTURE SPECIFICATION

LED CHIPS

Bridgelux 2835 LED

HOUSING

Aluminum body

WARRANTY

5 year warranty.

IP RATED



IP20 rated, dry location only.

LISTING


ETL listing, CE listing

PHOTOMETRIC CURVES & FIXTURE DIMENSIONS

COCO-LBE-9410




*UNIT: CD




AT 3000K, 90CRI
3000K- 110° BEAM

COCO-LBE-9411




*UNIT: CD




AT 3000K, 90CRI
3000K- 110° BEAM

COCO-LBE-9412



*UNIT: CD



AT 3000K, 90CRI
3000K- 110° BEAM