


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:24.00V I:0.6420A P:15.40W PF:1.000 Freq:0Hz Lamp Flux:1901.92x1 lm		
NAME: D81922410NO	TYPE:	WEIGHT:
SPEC.:D81922410NO-HNWDA012WC0100	DIM.: 1000*10*1.6mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 123.50 lm/W			
MODEL	D81922410NO	I _{max} (cd)	626.6	S/MH(C0/180)	1.30
NOMINAL POWER(W)	16	LOR(%)	100.0	S/MH(C90/270)	1.28
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	1901.9	h UP,DN(C0-180)	0.9,49.9
NOMINAL FLUX(lm)	1901.92	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.8,48.4
LAMPS INSIDE	1	h up(%)	1.7	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	24	h down(%)	98.3	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-12-04

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	618.0	619.6	618.0	617.4	614.6	614.5	615.1	616.8	0- 10	59.32	59.32	3.12,3.12
20	591.4	594.2	591.5	589.6	584.9	583.9	585.8	588.3	10- 20	170.9	230.2	12.1,12.1
30	545.5	549.5	546.1	542.9	536.6	535.0	537.9	540.8	20- 30	261.7	491.9	25.9,25.9
40	481.2	486.4	482.4	478.3	471.0	468.8	472.2	475.5	30- 40	320.1	812.0	42.7,42.7
50	399.3	404.6	401.0	395.1	386.4	385.8	387.4	392.7	40- 50	337.8	1150	60.5,60.5
60	301.1	305.5	303.2	297.1	289.5	288.4	289.7	294.5	50- 60	309.7	1459	76.7,76.7
70	188.4	194.5	190.5	187.5	181.1	177.5	179.5	182.1	60- 70	239.1	1699	89.3,89.3
80	75.93	80.89	76.57	77.19	72.79	68.97	68.97	71.45	70- 80	135.7	1834	96.4,96.4
90	7.214	6.309	3.199	6.736	4.539	3.880	1.718	6.390	80- 90	35.73	1870	98.3,98.3
100	3.007	2.480	2.224	2.493	1.774	1.709	1.613	1.670	90-100	2.793	1873	98.5,98.5
110	3.653	3.530	3.198	3.663	3.523	3.191	3.317	3.066	100-110	2.842	1876	98.6,98.6
120	5.296	5.106	4.888	5.228	5.104	4.569	4.577	4.661	110-120	4.137	1880	98.8,98.8
130	6.704	6.340	6.090	6.433	6.488	5.750	5.559	5.743	120-130	4.976	1885	99.1,99.1
140	7.741	7.195	7.026	7.401	7.590	6.984	6.334	6.406	130-140	5.130	1890	99.4,99.4
150	8.409	7.689	7.680	8.345	8.278	8.127	7.101	6.799	140-150	4.668	1895	99.6,99.6
160	9.184	8.169	8.836	9.345	8.984	9.150	8.658	7.479	150-160	3.801	1898	99.8,99.8
170	9.585	9.454	10.16	10.17	9.057	9.972	10.07	9.349	160-170	2.603	1901	99.9,99.9
180	9.512	11.05	11.23	11.32	9.512	11.03	11.21	11.32	170-180	0.9569	1902	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-12-04

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.6420A P:15.40W PF:1.000 Freq:0Hz Lamp Flux:1901.92x1 lm		
NAME: D81922410NO	TYPE:	WEIGHT:
SPEC.:D81922410NO-HNWDA012WC0100	DIM.: 1000*10*1.6mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*10	Shielding Angle:



LUMINANCE cd/(m2)		
G(180)	C0/180	C90/270
85	35627	34417
80	43726	44093
75	50528	51260
70	55082	55689
65	58357	58917
60	60229	60649
55	61422	61749
50	62121	62387
45	62573	62779


C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-12-04

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.6420A P:15.40W PF:1.000 Freq:0Hz Lamp Flux:1901.92x1 lm		
NAME: D81922410NO	TYPE:	WEIGHT:
SPEC.:D81922410NO-HNWDA012WC0100	DIM.: 1000*10*1.6mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.01	1.01	1.01	.98
1.0	1.03	.99	.95	1.01	.97	.93	.96	.93	.90	.92	.89	.87	.88	.86	.84	.82
2.0	.90	.83	.77	.88	.81	.76	.84	.79	.74	.80	.76	.72	.77	.73	.70	.68
3.0	.79	.70	.64	.77	.69	.63	.74	.67	.62	.71	.65	.60	.68	.63	.59	.57
4.0	.69	.61	.54	.68	.60	.53	.65	.58	.52	.63	.57	.51	.60	.55	.51	.48
5.0	.62	.53	.46	.61	.52	.46	.58	.51	.45	.56	.50	.44	.54	.48	.44	.42
6.0	.56	.47	.40	.55	.46	.40	.53	.45	.39	.51	.44	.39	.49	.43	.38	.36
7.0	.50	.42	.35	.50	.41	.35	.48	.40	.35	.46	.39	.34	.45	.39	.34	.32
8.0	.46	.37	.31	.45	.37	.31	.44	.36	.31	.42	.36	.31	.41	.35	.30	.28
9.0	.42	.34	.28	.41	.34	.28	.40	.33	.28	.39	.32	.28	.38	.32	.27	.26
10.0	.39	.31	.26	.38	.31	.25	.37	.30	.25	.36	.30	.25	.35	.29	.25	.23



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-12-04

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:24.00V I:0.6420A P:15.40W PF:1.000 Freq:0Hz Lamp Flux:1901.92x1 lm		
NAME: D81922410NO	TYPE:	WEIGHT:
SPEC.:D81922410NO-HNWNDA012WC0100	DIM.: 1000*10*1.6mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.313	.178	.056	.305	.174	.055	.291	.167	.053	.278	.160	.051	.266	.154	.050	
2.0	.294	.161	.049	.287	.158	.049	.275	.153	.047	.263	.148	.046	.252	.143	.045	
3.0	.272	.145	.043	.266	.143	.043	.255	.138	.042	.245	.134	.041	.235	.130	.040	
4.0	.251	.130	.038	.246	.129	.038	.236	.125	.037	.226	.122	.037	.218	.118	.036	
5.0	.232	.118	.034	.227	.117	.034	.218	.114	.033	.210	.111	.033	.202	.108	.032	
6.0	.215	.108	.031	.211	.106	.031	.203	.104	.030	.195	.101	.030	.188	.099	.029	
7.0	.200	.099	.028	.196	.098	.028	.189	.096	.028	.182	.093	.027	.176	.091	.027	
8.0	.187	.091	.026	.183	.090	.025	.177	.088	.025	.171	.087	.025	.165	.085	.025	
9.0	.175	.085	.024	.172	.084	.023	.166	.082	.023	.160	.080	.023	.155	.079	.023	
10.0	.164	.079	.022	.161	.078	.022	.156	.077	.022	.151	.075	.021	.147	.074	.021	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Ceiling Cavity Exitance Coefficients(CCEC)												
0.0	.203	.203	.203	.174	.174	.174	.119	.119	.119	.068	.068	.068	.022	.022	.022	
1.0	.193	.169	.147	.165	.145	.127	.113	.100	.088	.065	.058	.051	.021	.019	.016	
2.0	.186	.145	.111	.159	.125	.096	.109	.086	.067	.063	.050	.039	.020	.016	.013	
3.0	.178	.127	.087	.153	.110	.075	.105	.076	.053	.060	.045	.031	.019	.014	.010	
4.0	.170	.114	.071	.146	.099	.062	.101	.069	.044	.058	.040	.026	.019	.013	.008	
5.0	.163	.104	.060	.140	.090	.052	.096	.063	.037	.056	.037	.022	.018	.012	.007	
6.0	.156	.095	.052	.134	.083	.045	.092	.058	.032	.054	.034	.019	.017	.011	.006	
7.0	.149	.089	.046	.128	.077	.040	.089	.054	.029	.051	.032	.017	.017	.010	.006	
8.0	.143	.083	.042	.123	.072	.036	.085	.050	.026	.049	.030	.015	.016	.010	.005	
9.0	.136	.078	.038	.118	.068	.033	.081	.048	.024	.047	.028	.014	.015	.009	.005	
10.0	.131	.074	.036	.113	.064	.031	.078	.045	.022	.046	.027	.013	.015	.009	.004	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-12-04

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.6420A P:15.40W PF:1.000 Freq:0Hz Lamp Flux:1901.92x1 lm											
NAME: D81922410NO					TYPE:			WEIGHT:			
SPEC.:D81922410NO-HNWDA012WC0100					DIM.: 1000*10*1.6mm			SERIAL No.:			
MFR.: COLORS					SUR.:1000*10			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	25.0	26.5	25.3	26.8	27.0	25.0	26.6	25.3	26.8	27.0	
	3H	26.6	28.0	26.9	28.2	28.5	26.6	28.0	26.9	28.3	28.6
	4H	27.2	28.5	27.5	28.8	29.1	27.2	28.6	27.6	28.8	29.1
	6H	27.6	28.8	27.9	29.1	29.5	27.6	28.9	28.0	29.2	29.5
	8H	27.7	28.9	28.1	29.2	29.6	27.7	29.0	28.1	29.3	29.6
	12H	27.8	28.9	28.1	29.2	29.6	27.8	29.0	28.2	29.3	29.6
4H	2H	25.7	27.0	26.0	27.3	27.6	25.7	27.0	26.0	27.3	27.6
	3H	27.4	28.6	27.8	28.9	29.2	27.4	28.6	27.8	28.9	29.3
	4H	28.1	29.2	28.5	29.5	29.9	28.2	29.2	28.6	29.6	30.0
	6H	28.7	29.6	29.1	30.0	30.4	28.7	29.6	29.1	30.0	30.4
	8H	28.8	29.7	29.3	30.1	30.5	28.9	29.7	29.3	30.1	30.6
	12H	28.9	29.7	29.4	30.1	30.6	29.0	29.8	29.4	30.2	30.6
8H	4H	28.4	29.3	28.8	29.7	30.1	28.4	29.3	28.9	29.7	30.1
	6H	29.1	29.8	29.5	30.2	30.7	29.1	29.8	29.6	30.3	30.7
	8H	29.3	30.0	29.8	30.4	30.9	29.4	30.0	29.8	30.5	30.9
	12H	29.5	30.0	30.0	30.5	31.0	29.5	30.1	30.0	30.5	31.1
12H	4H	28.4	29.2	28.9	29.6	30.1	28.4	29.3	28.9	29.7	30.1
	6H	29.1	29.8	29.6	30.2	30.7	29.2	29.8	29.7	30.3	30.8
	8H	29.4	30.0	29.9	30.4	31.0	29.4	30.0	29.9	30.5	31.0
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.2					+ 0.1 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					

CIE Pub.117, 1902 lm Total Lamp Luminous Flux Correct ($8\log(F/F_0) = 2.2$)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-12-04

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.6420A P:15.40W PF:1.000 Freq:0Hz Lamp Flux:1901.92x1 lm		
NAME: D81922410NO	TYPE:	WEIGHT:
SPEC.:D81922410NO-HNWDA012WC0100	DIM.: 1000*10*1.6mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*10	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	56	45	38	56	44	37	54	44	37	31
0.80	66	55	47	65	54	47	63	53	46	39
1.00	75	64	56	74	63	56	71	64	55	48
1.25	82	71	64	80	71	64	78	69	63	55
1.50	87	77	70	85	76	69	82	74	68	60
2.00	94	85	79	92	84	78	88	82	76	68
2.50	98	90	84	96	89	83	92	86	81	72
3.00	101	94	89	99	93	88	95	90	85	76
4.00	106	100	95	103	98	94	98	94	91	81
5.00	108	103	99	105	101	97	101	97	94	84
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-12-04

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:24.00V I:0.6420A P:15.40W PF:1.000 Freq:0Hz Lamp Flux:1901.92x1 lm		
NAME: D81922410NO	TYPE:	WEIGHT:
SPEC.:D81922410NO-HNWDA012WC0100	DIM.: 1000*10*1.6mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*10	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-12-04

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:24.00V I:0.6420A P:15.40W PF:1.000 Freq:0Hz Lamp Flux:1901.92x1 lm		
NAME: D81922410NO	TYPE:	WEIGHT:
SPEC.:D81922410NO-HNWDA012WC0100	DIM.: 1000*10*1.6mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

Flux out:1431 lm




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-12-04

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:24.00V I:0.6420A P:15.40W PF:1.000 Freq:0Hz Lamp Flux:1901.92x1 lm		
NAME: D81922410NO	TYPE:	WEIGHT:
SPEC.:D81922410NO-HNWDA012WC0100	DIM.: 1000*10*1.6mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*10	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-12-04

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-12-04

Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.6420A P:15.40W PF:1.000 Freq:0Hz Lamp Flux:1901.92x1 lm		
NAME: D81922410NO	TYPE:	WEIGHT:
SPEC.:D81922410NO-HNWDA012WC0100	DIM.: 1000*10*1.6mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	626	626	626	627	626	626	626	627										
5	624	625	624	624	623	623	623	624										
10	618	620	618	617	615	615	615	617										
15	607	609	607	606	602	602	603	605										
20	591	594	592	590	585	584	586	588										
25	571	574	571	569	563	562	564	567										
30	545	549	546	543	537	535	538	541										
35	516	520	517	513	506	504	507	511										
40	481	486	482	478	471	469	472	475										
45	442	448	444	440	432	429	433	436										
50	399	405	401	395	386	386	387	393										
55	352	356	354	347	340	339	340	346										
60	301	306	303	297	290	288	290	294										
65	247	251	249	243	236	234	236	240										
70	188	195	190	188	181	177	180	182										
75	131	137	133	131	126	122	123	125										
80	75.9	80.9	76.6	77.2	72.8	69.0	69.0	71.4										
85	31.1	34.2	30.0	32.2	28.9	26.1	25.2	27.9										
90	7.21	6.31	3.20	6.74	4.54	3.88	1.72	6.39										
95	3.89	2.50	2.33	2.62	1.42	1.39	0.88	2.89										
100	3.01	2.48	2.22	2.49	1.77	1.71	1.61	1.67										
105	2.86	2.92	2.47	2.98	2.65	2.50	2.60	2.42										
110	3.65	3.53	3.20	3.66	3.52	3.19	3.32	3.07										
115	4.49	4.35	4.12	4.48	4.32	3.90	4.00	3.90										
120	5.30	5.11	4.89	5.23	5.10	4.57	4.58	4.66										
125	6.05	5.77	5.54	5.87	5.82	5.12	5.10	5.28										
130	6.70	6.34	6.09	6.43	6.49	5.75	5.56	5.74										
135	7.27	6.81	6.58	6.93	7.08	6.37	5.98	6.18										
140	7.74	7.20	7.03	7.40	7.59	6.98	6.33	6.41										
145	8.08	7.47	7.37	7.85	8.00	7.56	6.65	6.60										
150	8.41	7.69	7.68	8.35	8.28	8.13	7.10	6.80										
155	8.77	7.90	8.13	8.86	8.66	8.66	7.81	7.01										
160	9.18	8.17	8.84	9.34	8.98	9.15	8.66	7.48										
165	9.60	8.64	9.52	9.75	9.22	9.52	9.40	8.29										
170	9.59	9.45	10.2	10.2	9.06	9.97	10.1	9.35										
175	9.24	10.3	10.8	10.7	8.80	10.4	10.7	10.4										
180	9.51	11.0	11.2	11.3	9.51	11.0	11.2	11.3										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-12-04

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: