


## LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:24.00V I:0.8757A P:21.02W PF:1.000 Freq:0Hz Lamp Flux:3192.13x1 lm		
NAME: D82402410NO	TYPE:	WEIGHT:
SPEC.:D82402410NO-8NWDA012WC0100	DIM.: 1000*10*1.6mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 151.90 lm/W			
MODEL	D82402410NO	I <sub>max</sub> (cd)	1022	S/MH(C0/180)	1.28
NOMINAL POWER(W)	20	LOR(%)	100.0	S/MH(C90/270)	1.30
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	3192.1	h UP,DN(C0-180)	0.9,48.6
NOMINAL FLUX(lm)	3192.13	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.8,49.6
LAMPS INSIDE	1	h up(%)	1.7	CIBSE SHR NOM	1.50
TEST VOLTAGE(V)	24	h down(%)	98.3	CIBSE SHR MAX	1.50



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-12-03

g Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

## ZONAL FLUX DIAGRAM

### ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	1004	1008	1007	1008	1012	1009	1005	1004	0- 10	96.77	96.77	3.03,3.03
20	958.3	965.5	966.0	968.6	974.3	968.2	962.5	959.5	10- 20	279.6	376.4	11.8,11.8
30	881.7	893.7	896.7	900.8	908.8	899.1	891.4	885.5	20- 30	430.6	806.9	25.3,25.3
40	773.9	790.9	797.5	803.7	814.4	801.7	790.5	780.7	30- 40	530.7	1338	41.9,41.9
50	634.8	656.8	667.9	676.5	690.6	674.3	659.5	644.9	40- 50	564.7	1902	59.6,59.6
60	465.7	493.0	508.4	521.1	539.3	519.6	500.1	479.9	50- 60	523.9	2426	76,76
70	274.0	301.6	321.7	339.2	360.2	340.4	313.2	291.9	60- 70	408.0	2834	88.8,88.8
80	88.96	114.0	128.1	156.8	172.6	153.5	124.1	106.3	70- 80	234.6	3069	96.1,96.1
90	6.181	13.31	5.247	23.49	28.37	21.48	3.450	15.09	80- 90	67.63	3137	98.3,98.3
100	4.534	4.591	3.820	4.336	2.679	2.657	2.736	3.295	90-100	6.634	3143	98.5,98.5
110	7.074	6.500	5.588	6.083	5.207	5.124	5.713	5.610	100-110	4.916	3148	98.6,98.6
120	9.626	8.834	8.229	8.674	7.987	7.352	7.987	8.394	110-120	7.089	3155	98.8,98.8
130	11.73	10.50	10.07	10.83	10.43	9.476	9.810	10.36	120-130	8.449	3164	99.1,99.1
140	13.10	11.57	11.43	12.43	12.32	11.55	11.12	11.45	130-140	8.640	3172	99.4,99.4
150	13.84	12.13	12.53	13.89	13.44	13.51	12.05	11.94	140-150	7.774	3180	99.6,99.6
160	14.81	12.91	14.62	15.38	14.53	15.05	14.29	12.74	150-160	6.267	3186	99.8,99.8
170	15.13	15.28	16.71	16.63	14.57	16.34	16.47	15.22	160-170	4.249	3191	100,100
180	14.96	18.04	18.30	18.50	14.94	18.05	18.35	18.50	170-180	1.553	3192	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG  
 C Interval: 45.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JYH  
 Test Date:2020-12-03

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.950m [K=1.0000]  
 Remarks:

### LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.8757A P:21.02W PF:1.000 Freq:0Hz Lamp Flux:3192.13x1 lm		
NAME: D82402410NO	TYPE:	WEIGHT:
SPEC.:D82402410NO-8NWDA012WC0100	DIM.: 1000*10*1.6mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*10	Shielding Angle:



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	3348	5745
80	5123	7379
75	6775	8632
70	8011	9407
65	8794	9898
60	9315	10167
55	9655	10318
50	9876	10391
45	10016	10417


C Range: 0 - 360DEG  
 C Interval: 45.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JYH  
 Test Date:2020-12-03

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.950m [K=1.0000]  
 Remarks:

## CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.8757A P:21.02W PF:1.000 Freq:0Hz Lamp Flux:3192.13x1 lm		
NAME: D82402410NO	TYPE:	WEIGHT:
SPEC.:D82402410NO-8NWDA012WC0100	DIM.: 1000*10*1.6mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

r <sub>cc</sub>	80%			70%			50%			30%			10%			0
r <sub>w</sub>	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r <sub>fc</sub>	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio                      Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.00	1.00	1.00	.98
1.0	1.03	.99	.95	1.01	.97	.93	.96	.93	.90	.92	.89	.87	.88	.86	.84	.82
2.0	.89	.82	.77	.87	.81	.75	.84	.78	.73	.80	.75	.72	.77	.73	.70	.67
3.0	.78	.70	.63	.77	.69	.63	.73	.67	.61	.70	.65	.60	.67	.63	.59	.56
4.0	.69	.60	.53	.68	.59	.53	.65	.58	.52	.62	.56	.51	.60	.55	.50	.48
5.0	.62	.52	.46	.60	.52	.45	.58	.50	.45	.56	.49	.44	.54	.48	.43	.41
6.0	.55	.46	.40	.54	.46	.39	.52	.45	.39	.50	.44	.38	.49	.43	.38	.36
7.0	.50	.41	.35	.49	.41	.35	.47	.40	.34	.46	.39	.34	.44	.38	.34	.31
8.0	.46	.37	.31	.45	.37	.31	.43	.36	.31	.42	.35	.30	.41	.34	.30	.28
9.0	.42	.33	.28	.41	.33	.28	.40	.33	.27	.39	.32	.27	.37	.31	.27	.25
10.0	.38	.30	.25	.38	.30	.25	.37	.30	.25	.36	.29	.25	.35	.29	.24	.23



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-12-03

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

WEC AND CCEC

Test:U:24.00V I:0.8757A P:21.02W PF:1.000 Freq:0Hz Lamp Flux:3192.13x1 lm		
NAME: D82402410NO	TYPE:	WEIGHT:
SPEC.:D82402410NO-8NWDA012WC0100	DIM.: 1000*10*1.6mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.317	.180	.057	.309	.177	.056	.295	.169	.054	.282	.163	.052	.270	.156	.050	
2.0	.297	.163	.050	.291	.160	.049	.278	.155	.048	.266	.149	.047	.255	.144	.046	
3.0	.274	.146	.044	.268	.144	.043	.257	.139	.042	.247	.135	.041	.237	.131	.041	
4.0	.253	.131	.039	.248	.130	.038	.237	.126	.038	.228	.123	.037	.220	.119	.036	
5.0	.233	.119	.034	.229	.117	.034	.220	.114	.034	.211	.112	.033	.204	.109	.033	
6.0	.216	.108	.031	.212	.107	.031	.204	.105	.030	.196	.102	.030	.189	.100	.030	
7.0	.201	.099	.028	.197	.098	.028	.190	.096	.028	.183	.094	.027	.177	.092	.027	
8.0	.187	.092	.026	.184	.091	.026	.178	.089	.025	.172	.087	.025	.166	.085	.025	
9.0	.176	.085	.024	.172	.084	.024	.167	.082	.023	.161	.081	.023	.156	.079	.023	
10.0	.165	.079	.022	.162	.078	.022	.157	.077	.022	.152	.075	.021	.147	.074	.021	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Ceiling Cavity Exitance Coefficients(CCEC)												
0.0	.204	.204	.204	.174	.174	.174	.119	.119	.119	.068	.068	.068	.022	.022	.022	
1.0	.194	.169	.147	.166	.145	.127	.114	.100	.088	.065	.058	.051	.021	.019	.016	
2.0	.186	.145	.111	.160	.125	.096	.109	.087	.067	.063	.050	.039	.020	.016	.013	
3.0	.179	.128	.087	.153	.110	.076	.105	.077	.053	.061	.045	.031	.020	.015	.010	
4.0	.171	.115	.071	.147	.099	.062	.101	.069	.044	.058	.040	.026	.019	.013	.008	
5.0	.164	.104	.060	.141	.090	.053	.097	.063	.037	.056	.037	.022	.018	.012	.007	
6.0	.157	.096	.052	.135	.083	.046	.093	.058	.032	.054	.034	.019	.017	.011	.006	
7.0	.150	.089	.047	.129	.077	.041	.089	.054	.029	.052	.032	.017	.017	.010	.006	
8.0	.143	.083	.042	.123	.072	.037	.085	.051	.026	.050	.030	.016	.016	.010	.005	
9.0	.137	.078	.039	.118	.068	.034	.082	.048	.024	.048	.028	.014	.015	.009	.005	
10.0	.132	.074	.036	.113	.064	.031	.079	.045	.022	.046	.027	.013	.015	.009	.004	

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-12-03

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.8757A P:21.02W PF:1.000 Freq:0Hz Lamp Flux:3192.13x1 lm											
NAME: D82402410NO					TYPE:			WEIGHT:			
SPEC.:D82402410NO-8NWDA012WC0100					DIM.: 1000*10*1.6mm			SERIAL No.:			
MFR.: COLORS					SUR.:1000*10			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	Viewed crosswise					Viewed endwise					
x = 2H y = 2H	16.6	18.1	16.9	18.4	18.6	16.9	18.4	17.2	18.7	18.9	
	3H	18.0	19.4	18.3	19.7	20.0	18.5	19.9	18.8	20.2	20.4
	4H	18.5	19.8	18.8	20.1	20.4	19.1	20.4	19.5	20.7	21.0
	6H	18.8	20.0	19.1	20.3	20.6	19.5	20.8	19.9	21.1	21.4
	8H	18.8	20.0	19.2	20.3	20.7	19.6	20.8	20.0	21.2	21.5
	12H	18.8	20.0	19.2	20.3	20.6	19.7	20.8	20.1	21.2	21.5
4H	2H	17.3	18.6	17.6	18.9	19.2	17.5	18.8	17.8	19.1	19.4
	3H	18.8	20.0	19.2	20.3	20.7	19.2	20.4	19.6	20.7	21.1
	4H	19.4	20.5	19.8	20.9	21.2	20.0	21.0	20.4	21.4	21.8
	6H	19.8	20.7	20.2	21.1	21.5	20.5	21.4	20.9	21.8	22.2
	8H	19.9	20.8	20.3	21.2	21.6	20.6	21.5	21.1	21.9	22.4
	12H	19.9	20.7	20.3	21.1	21.6	20.7	21.5	21.2	22.0	22.4
8H	4H	19.7	20.6	20.1	21.0	21.4	20.2	21.1	20.6	21.5	21.9
	6H	20.2	20.9	20.6	21.3	21.8	20.8	21.6	21.3	22.0	22.5
	8H	20.3	21.0	20.8	21.4	21.9	21.0	21.7	21.5	22.2	22.6
	12H	20.4	21.0	20.9	21.4	21.9	21.2	21.8	21.7	22.2	22.8
12H	4H	19.7	20.5	20.2	20.9	21.4	20.2	21.0	20.6	21.4	21.8
	6H	20.2	20.9	20.7	21.3	21.8	20.8	21.5	21.3	22.0	22.4
	8H	20.4	21.0	20.9	21.4	22.0	21.1	21.7	21.6	22.1	22.7
Variations with the observer position at spacings:											
S = 1.0H	+ 0.2 / - 0.2					+ 0.1 / - 0.2					
1.5H	+ 0.2 / - 0.4					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.4					+ 0.2 / - 0.3					

CIE Pub.117, 3192 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 4.0)

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-12-03

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

### UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.8757A P:21.02W PF:1.000 Freq:0Hz Lamp Flux:3192.13x1 lm		
NAME: D82402410NO	TYPE:	WEIGHT:
SPEC.:D82402410NO-8NWDA012WC0100	DIM.: 1000*10*1.6mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*10	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	56	44	37	55	44	37	54	43	37	30
0.80	66	54	47	65	54	46	63	53	46	39
1.00	74	63	56	73	62	55	71	64	55	47
1.25	82	71	63	80	70	63	77	68	62	54
1.50	87	76	69	85	75	69	82	74	68	60
2.00	94	85	78	92	84	77	88	81	76	67
2.50	98	90	83	96	88	82	91	85	80	72
3.00	101	94	88	99	92	87	95	89	85	76
4.00	105	99	95	103	98	93	98	94	90	81
5.00	108	103	99	105	101	97	100	97	94	84
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG  
 C Interval: 45.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JYH  
 Test Date:2020-12-03

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.950m [K=1.0000]  
 Remarks:

### ISOCANDELA DIAGRAM

Test:U:24.00V I:0.8757A P:21.02W PF:1.000 Freq:0Hz Lamp Flux:3192.13x1 lm		
NAME: D82402410NO	TYPE:	WEIGHT:
SPEC.:D82402410NO-8NWDA012WC0100	DIM.: 1000*10*1.6mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*10	Shielding Angle:



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-12-03


deg Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:



### AAI Figure

Test:U:24.00V I:0.8757A P:21.02W PF:1.000 Freq:0Hz Lamp Flux:3192.13x1 lm		
NAME: D82402410NO	TYPE:	WEIGHT:
SPEC.:D82402410NO-8NWDA012WC0100	DIM.: 1000*10*1.6mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

Flux out:2426 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-12-03

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

### ISOLUX DIAGRAM


Test:U:24.00V I:0.8757A P:21.02W PF:1.000 Freq:0Hz Lamp Flux:3192.13x1 lm		
NAME: D82402410NO	TYPE:	WEIGHT:
SPEC.:D82402410NO-8NWDA012WC0100	DIM.: 1000*10*1.6mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*10	Shielding Angle:



C Range: 0 - 360DEG  
 C Interval: 45.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JYH  
 Test Date:2020-12-03

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.950m [K=1.0000]  
 Remarks:

### Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: JYH  
Test Date: 2020-12-03

Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity: 65.0%  
Test Distance: 10.950m [K=1.0000]  
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.8757A P:21.02W PF:1.000 Freq:0Hz Lamp Flux:3192.13x1 lm		
NAME: D82402410NO	TYPE:	WEIGHT:
SPEC.:D82402410NO-8NWDA012WC0100	DIM.: 1000*10*1.6mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	1021	1022	1019	1019	1021	1022	1019	1019										
5	1017	1018	1016	1017	1020	1018	1015	1015										
10	1004	1008	1007	1008	1012	1009	1005	1004										
15	985	990	990	992	996	992	987	985										
20	958	966	966	969	974	968	962	960										
25	924	933	935	938	945	937	930	926										
30	882	894	897	901	909	899	891	886										
35	832	846	851	856	865	854	845	837										
40	774	791	798	804	814	802	791	781										
45	708	728	737	744	756	742	729	717										
50	635	657	668	676	691	674	660	645										
55	554	578	592	602	618	600	583	566										
60	466	493	508	521	539	520	500	480										
65	372	399	418	434	454	432	409	388										
70	274	302	322	339	360	340	313	292										
75	175	204	223	247	266	246	217	196										
80	89.0	114	128	157	173	154	124	106										
85	29.2	45.8	50.1	77.8	87.7	74.2	47.5	41.5										
90	6.18	13.3	5.25	23.5	28.4	21.5	3.45	15.1										
95	4.13	5.75	3.89	5.73	5.32	4.01	1.47	8.05										
100	4.53	4.59	3.82	4.34	2.68	2.66	2.74	3.30										
105	5.70	5.40	4.37	5.06	3.73	3.91	4.36	4.54										
110	7.07	6.50	5.59	6.08	5.21	5.12	5.71	5.61										
115	8.38	7.74	6.98	7.41	6.62	6.27	6.94	7.10										
120	9.63	8.83	8.23	8.67	7.99	7.35	7.99	8.39										
125	10.7	9.77	9.23	9.82	9.28	8.40	8.94	9.51										
130	11.7	10.5	10.1	10.8	10.4	9.48	9.81	10.4										
135	12.5	11.1	10.7	11.7	11.4	10.5	10.5	11.1										
140	13.1	11.6	11.4	12.4	12.3	11.5	11.1	11.4										
145	13.5	11.9	11.9	13.2	13.0	12.5	11.5	11.7										
150	13.8	12.1	12.5	13.9	13.4	13.5	12.1	11.9										
155	14.3	12.4	13.5	14.7	14.0	14.4	13.0	12.3										
160	14.8	12.9	14.6	15.4	14.5	15.0	14.3	12.7										
165	15.3	13.9	15.7	16.0	14.9	15.7	15.4	13.7										
170	15.1	15.3	16.7	16.6	14.6	16.3	16.5	15.2										
175	14.5	16.8	17.6	17.5	14.0	17.1	17.5	16.9										
180	15.0	18.0	18.3	18.5	14.9	18.0	18.3	18.5										

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-12-03

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks: