

PEG

METROLINE

LOW-VOLTAGE RAIL SYSTEM

As part of the Metroline Low-Voltage Rail System, these modules provide soft glowing light for general illumination or decorative accent lighting. Ideal for adding visual interest in the space with a soft glow. Combine with the Double Peg companion module for greater variety.



ORDERING INFORMATION

MODEL	CCT	FINISH	CRI	WATT	VOLT	DIMMING
ML-LWE-9361P	27 2700K	W WHITE	90 90CRI	4 4 WATT	48 48 VOLT	N NON-DIMMING
	30 3000K	B BLACK				D 1-10V DIMMING (DOWN TO 5%)
	35 3500K					
	40 4000K					

EXAMPLE ORDERING CODE: ML-LWE-9361P-27-W-90-4-48-D

LUMEN OUTPUT*

	ML-LWE-9361P			
Wattage	4W			
CCT (90 CRI)	2700K	3000K	3500K	4000K
Lumen Package	257 lm	268 lm	273 lm	278 lm

*DELIVERED LUMEN VALUES SHOWN ARE BASED ON EXTRAPOLATED DATA FROM 3000K 90CRI PHOTOMETRIC TESTING.

THIS PRODUCT IS PART OF THE MODULAR METROLINE SYSTEM.
TO SPECIFY RAIL AND POWER SUPPLY OPTIONS FOR A COMPLETE SYSTEM, VISIT:

[HTTPS://COSINELTG.COM/METROLINE-SERIES/#RESOURCES](https://cosineltg.com/metroline-series/#resources)

FIXTURE SPECIFICATIONS

LED CHIPS

BRIDGELUX LED
INPUT POWER: 4W
5% DIMMING RANGE
67 LM/W AVERAGE EFFICACY

CONSTRUCTION

ALUMINUM BODY; BLACK AND WHITE PAINTED
FINISH OPTIONS; ACRYLIC OPTICAL ACCESSORY

WARRANTY

5 YEAR WARRANTY

LISTINGS

IP20, DRY LOCATION ONLY
ETL, CE


ML-LWE-9361P



PHOTOMETRIC CURVES

ML-LWE-9361P

*UNIT: CD



AT 3000K, 90CRI
3000K- 124° BEAM

THIS PRODUCT IS PART OF THE MODULAR METROLINE SYSTEM.
TO SPECIFY RAIL AND POWER SUPPLY OPTIONS FOR A COMPLETE SYSTEM, VISIT:

[HTTPS://COSINELTG.COM/METROLINE-SERIES/#RESOURCES](https://cosineltg.com/metroline-series/#resources)