

METROLINE

LOW-VOLTAGE RAIL SYSTEM

DIRECTIONAL CYLINDERS

Project _____

Date _____

Type _____



ORDERING INFORMATION

MODEL	CCT	FINISH	CRI	WATT	BEAM ANGLE	VOLT	DIMMING
ML-HTE-9674	27 - 2700K 30 - 3000K 35 - 3500K 40 - 4000K	W - White B - Black	90 - 90CRI	4 - 4W	15 - 15° 36 - 36° 50 - 50°	48 - 48V	N - Non Dim D - 1-10V Dim
ML-HTE-9675				10 - 10W			
ML-HTE-							

LUMEN OUTPUT & WATTAGE

	ML-HTE-9674		ML-HTE-9675	
Wattage	4W		10W	
Color Temperature	2700K / 3000K	3500K / 4000K	2700K / 3000K	3500K / 4000K
Lumen Package	399 lm	420 lm	778 lm	855 lm

FIXTURE SPECIFICATION

LED CHIPS
CREE LED

HOUSING
Aluminum body

WARRANTY
5 year warranty


IP RATED
IP20 rated, dry location only

LISTING
ETL listing, CE listing






PHOTOMETRIC CURVES


ML-HTE-9674



*UNIT: CD



ML-HTE-9675



*UNIT: CD

