

METROLINE

LOW-VOLTAGE RAIL SYSTEM

MEDALLION

Project _____

Date _____

Type _____



ORDERING INFORMATION

MODEL	CCT	FINISH	CRI	WATT	BEAM ANGLE	VOLT	DIMMING
ML-HTE-9676	27 - 2700K 30 - 3000K 35 - 3500K 40 - 4000K	W - White B - Black	90 - 90CRI	6 - 6W	12 - 12° 24 - 24° 38 - 38° 45 - 45° 60 - 60°	48 - 48V	N - Non Dim D - 1-10V Dim
ML-HTE-9676							

LUMEN OUTPUT & WATTAGE

	ML-HTE-9676	
Wattage	6W	
Color Temperature	2700K / 3000K	3500K / 4000K
Lumen Package	502 lm	552 lm

FIXTURE SPECIFICATION

LED CHIPS

Bridgelux C6 LED

HOUSING

Aluminum body

WARRANTY

5 year warranty

IP RATED


IP20 rated, dry location only

LISTING


ETL listing, CE listing

PHOTOMETRIC CURVES


ML-HTE-9676




*UNIT: CD




AT 3000K, 90CRI
3000K- 12° BEAM




AT 3000K, 90CRI
3000K- 18.6° BEAM



AT 3000K, 90CRI
3000K- 35° BEAM



AT 3000K, 90CRI
3000K- 47° BEAM



AT 3000K, 90CRI
3000K- 58° BEAM