

METROLINE

LOW-VOLTAGE RAIL SYSTEM

TOOB

Project _____

Date _____

Type _____



ORDERING INFORMATION

MODEL	CCT	FINISH	CRI	WATT	LENS DEGREE	VOLT	DIMMING
ML-LPE-9201	27 - 2700K 30 - 3000K 35 - 3500K 40 - 4000K	W - White B - Black	90 - 90CRI	6 - 6W	15 - 15° 36 - 36° 50 - 50°	48 - 48V	N - Non Dim D - 1-10V Dim
ML-LPE-9201							

LUMEN OUTPUT & WATTAGE

	ML-LPE-9201	
Wattage	6W	
Color Temperature	2700K / 3000K	3500K / 4000K
Lumen Package	501 lm	564 lm

FIXTURE SPECIFICATION

LED CHIPS

Bridgelux LED

HOUSING

Aluminum body

WARRANTY

5 year warranty

IP RATED

IP20 rated, dry location only

LISTING

ETL listing, CE listing




PHOTOMETRIC CURVES

ML-LPE-9201




*UNIT: CD




AT 3000K, 90CRI
3000K- 22.6° BEAM

*UNIT: CD



AT 3000K, 90CRI
3000K- 30° BEAM

*UNIT: CD



AT 3000K, 90CRI
3000K- 45° BEAM