



Light Output Ratio:	87.8%	
Luminaire Power:	20.1 W	
SHR Nominal:	0.00	Calculated using the TM5
SHR Maximum:	0.20	fine grid method.



C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2023-06-27

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.444
Humidity: 65.0%
Test Distance: 10.214m [K=1.0000]
Remarks:

LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:19.148V I:1.0499A P:20.104W PF:1.0000 Freq:49.99Hz Lamp Flux:2012x1 lm		
NAME: LYE-8049A	TYPE: LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.: 230091
MFR.: Cosine	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 87.89 lm/W			
MODEL	CXB1304-3000K	I _{max} (cd)	22265	S/MH (C0/180)	0.25
NOMINAL POWER (W)	20.2	LOR (%)	87.8	S/MH (C90/270)	0.19
RATED VOLTAGE (V)	19.3	TOTAL FLUX (lm)	1766.9	η UP, DN (C0-180)	0.0, 44.8
NOMINAL FLUX (lm)	2012	CIE CLASS	DIRECT	η UP, DN (C180-360)	0.0, 43.0
LAMPS INSIDE	1	η up (%)	0.0	CIBSE SHR NOM	0.00
TEST VOLTAGE (V)	19.3	η down (%)	87.8	CIBSE SHR MAX	0.20

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM

C0 PLANE ISOLUX DIAGRAM (UNIT:lx)


C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2023-06-27

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.444
Humidity: 65.0%
Test Distance: 10.214m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM
ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	428.3	423.9	392.0	474.7	561.4	437.7	317.5	334.6	0- 10	985.0	985.0	55.7,49
20	46.38	46.01	44.64	47.45	50.38	45.97	41.82	42.74	10- 20	358.4	1343	76,66.8
30	22.13	21.60	21.56	22.67	23.24	22.06	21.11	21.54	20- 30	141.9	1485	84.1,73.8
40	12.70	12.45	12.61	13.34	13.42	12.90	12.54	12.69	30- 40	104.9	1590	90,79
50	7.620	7.610	7.995	8.362	8.191	7.959	7.807	7.793	40- 50	78.38	1669	94.4,82.9
60	3.841	3.942	4.059	4.111	4.077	3.981	3.894	3.870	50- 60	50.44	1719	97.3,85.4
70	2.038	2.124	2.215	2.237	2.187	2.143	2.082	2.056	60- 70	29.59	1749	99,86.9
80	0.7233	0.7727	0.8341	0.8534	0.8370	0.7944	0.7407	0.7142	70- 80	15.18	1764	99.8,87.7
90	0.0152	0.0132	0.0096	0.0100	0.0120	0.0140	0.0112	0.0120	80- 90	3.171	1767	100,87.8
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:×10cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 30.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2023-06-27

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.444
 Humidity:65.0%
 Test Distance:10.214m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:19.148V I:1.0499A P:20.104W PF:1.0000 Freq:49.99Hz Lamp Flux:2012x1 lm		
NAME: LYE-8049A	TYPE: LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.: 230091
MFR.: Cosine	SUR.:	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	5580	7794
80	10413	12008
75	13073	14458
70	14900	16192
65	16882	18020
60	19206	20294
55	23467	23868
50	29637	31093
45	35251	34981


C Range: 0 - 360DEG
 C Interval: 30.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2023-06-27

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.444
 Humidity:65.0%
 Test Distance:10.214m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:19.148V I:1.0499A P:20.104W PF:1.0000 Freq:49.99Hz Lamp Flux:2012x1 lm		
NAME: LYE-8049A	TYPE: LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.: 230091
MFR.: Cosine	SUR.:	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.05	1.05	1.05	1.02	1.02	1.02	.98	.98	.98	.93	.93	.93	.90	.90	.90	.88
1.0	.99	.97	.95	.97	.95	.94	.93	.92	.91	.90	.89	.88	.87	.86	.86	.84
2.0	.94	.91	.89	.92	.90	.88	.90	.88	.86	.87	.85	.84	.85	.83	.82	.81
3.0	.90	.86	.84	.89	.86	.83	.86	.84	.82	.84	.82	.81	.82	.81	.79	.78
4.0	.86	.83	.80	.85	.82	.79	.84	.81	.79	.82	.80	.78	.80	.78	.77	.76
5.0	.83	.80	.77	.82	.79	.76	.81	.78	.76	.80	.77	.75	.78	.76	.75	.74
6.0	.81	.77	.74	.80	.77	.74	.79	.76	.74	.78	.75	.73	.77	.74	.73	.72
7.0	.78	.75	.72	.78	.74	.72	.77	.74	.72	.76	.73	.71	.75	.73	.71	.70
8.0	.76	.73	.70	.76	.73	.70	.75	.72	.70	.74	.72	.70	.74	.71	.70	.69
9.0	.75	.71	.69	.74	.71	.69	.74	.71	.69	.73	.70	.68	.72	.70	.68	.67
10.0	.73	.70	.68	.73	.70	.67	.72	.69	.67	.72	.69	.67	.71	.69	.67	.66



C Range: 0 - 360DEG
 C Interval: 30.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2023-06-27

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.444
 Humidity:65.0%
 Test Distance:10.214m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:19.148V I:1.0499A P:20.104W PF:1.0000 Freq:49.99Hz Lamp Flux:2012x1 lm										
NAME: LYE-8049A					TYPE: LED			WEIGHT:		
SPEC.:					DIM.:			SERIAL No.: 230091		
MFR.: Cosine					SUR.:			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	16.0	16.7	16.2	16.8	17.0	16.1	16.8	16.3	16.9	17.1
3H	16.8	17.4	17.0	17.6	17.8	16.9	17.6	17.2	17.8	17.9
4H	17.1	17.7	17.3	17.9	18.1	17.3	17.9	17.5	18.1	18.3
6H	17.3	17.8	17.5	18.1	18.3	17.5	18.1	17.8	18.3	18.5
8H	17.3	17.8	17.6	18.1	18.3	17.6	18.1	17.9	18.4	18.6
12H	17.3	17.8	17.6	18.1	18.3	17.6	18.1	17.9	18.4	18.6
4H 2H	16.4	17.0	16.6	17.2	17.4	16.5	17.0	16.7	17.3	17.5
3H	17.3	17.8	17.6	18.1	18.3	17.4	18.0	17.7	18.2	18.5
4H	17.7	18.2	18.0	18.5	18.8	17.9	18.4	18.2	18.7	19.0
6H	17.9	18.4	18.3	18.7	19.0	18.2	18.6	18.6	18.9	19.3
8H	18.0	18.4	18.4	18.7	19.1	18.3	18.7	18.6	19.0	19.4
12H	18.0	18.4	18.4	18.7	19.1	18.3	18.6	18.7	19.0	19.4
8H 4H	17.8	18.2	18.2	18.6	18.9	18.0	18.4	18.4	18.7	19.1
6H	18.1	18.5	18.6	18.9	19.3	18.4	18.7	18.8	19.1	19.5
8H	18.2	18.5	18.7	18.9	19.4	18.5	18.8	18.9	19.2	19.6
12H	18.2	18.5	18.7	18.9	19.4	18.5	18.8	19.0	19.2	19.7
12H 4H	17.8	18.1	18.2	18.5	18.9	17.9	18.3	18.4	18.7	19.1
6H	18.1	18.4	18.6	18.8	19.3	18.4	18.7	18.8	19.1	19.5
8H	18.2	18.5	18.7	18.9	19.4	18.5	18.7	18.9	19.2	19.7
Variations with the observer position at spacings(CIE Pub.117):										
S = 1.0H	+ 0.5 / - 0.6					+ 0.5 / - 0.6				
1.5H	+ 0.3 / - 0.3					+ 0.3 / - 0.4				
2.0H	+ 1.2 / - 0.9					+ 1.0 / - 0.7				


CIE Pub.117, 2012 lm Total Lamp Luminous Flux Correct ($8\log(F/F_0) = 2.4$)
Area: 0.004 m2

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2023-06-27

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.444
Humidity:65.0%
Test Distance:10.214m [K=1.0000]
Remarks:

AAI Figure

Test:U:19.148V I:1.0499A P:20.104W PF:1.0000 Freq:49.99Hz Lamp Flux:2012x1 lm		
NAME: LYE-8049A	TYPE: LED	WEIGHT:
SPEC.:	DIM.:	SERIAL No.: 230091
MFR.: Cosine	SUR.:	Shielding Angle:



Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2023-06-27

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.444
Humidity:65.0%
Test Distance:10.214m [K=1.0000]
Remarks:

